


# TRAVI HEA EN 10025 - EN 10034 HEA BEAMS EN 10025 - EN 10034



| profilo e dimensioni in mm / section and dimensions in mm |     |     |      |      | peso<br>weight<br>Kg / Mt |
|---|-----|-----|------|------|---------------------------|
| HE  | h   | b   | a    | e    |                           |
| 100   | 96  | 100 | 5,0  | 8,0  | 16,700                    |
| 120   | 114 | 120 | 5,0  | 8,0  | 19,900                    |
| 140   | 133 | 140 | 5,5  | 8,5  | 24,700                    |
| 160   | 152 | 160 | 6,0  | 9,0  | 30,400                    |
| 180   | 171 | 180 | 6,0  | 9,5  | 35,500                    |
| 200   | 190 | 200 | 6,5  | 10,0 | 42,300                    |
| 220   | 210 | 220 | 7,0  | 11,0 | 50,500                    |
| 240   | 230 | 240 | 7,5  | 12,0 | 60,300                    |
| 260   | 250 | 260 | 7,5  | 12,5 | 68,200                    |
| 280   | 270 | 280 | 8,0  | 13,0 | 76,400                    |
| 300   | 290 | 300 | 8,5  | 14,0 | 88,300                    |
| 320   | 310 | 300 | 9,0  | 15,5 | 97,600                    |
| 340   | 330 | 300 | 9,5  | 16,5 | 105,000                   |
| 360   | 350 | 300 | 10,0 | 17,5 | 112,000                   |
| 400   | 390 | 300 | 11,0 | 19,0 | 125,000                   |
| 450   | 440 | 300 | 11,5 | 21,0 | 140,000                   |
| 500   | 490 | 300 | 12,0 | 23,0 | 155,000                   |
| 550   | 540 | 300 | 12,5 | 24,0 | 166,000                   |
| 600   | 590 | 300 | 13,0 | 25,0 | 178,000                   |
| 650   | 640 | 300 | 13,5 | 26,0 | 190,000                   |
| 700   | 690 | 300 | 14,5 | 27,0 | 204,000                   |
| 800   | 790 | 300 | 15,0 | 28,0 | 224,000                   |
| 900   | 890 | 300 | 16,0 | 30,0 | 252,000                   |
| 1000  | 990 | 300 | 16,5 | 31,0 | 272,000                   |

Ampia gamma disponibile anche in qualità S355J2