


TRAVI HEB EN 10025 - EN 10034

HEB BEAMS EN 10025 - EN 10034



profilo e dimensioni in mm/ section and dimensions in mm					peso weight Kg / Mt
HE	h	b	a	e	
100	100	100	6,0	10,0	20,400
120	120	120	6,5	11,0	26,700
140	140	140	7,0	12,0	33,700
160	160	160	8,0	13,0	42,600
180	180	180	8,5	14,0	51,200
200	200	200	9,0	15,0	61,300
220	220	220	9,5	16,0	71,500
240	240	240	10,0	17,0	83,200
260	260	260	10,0	17,5	93,000
280	280	280	10,5	18,0	103,000
300	300	300	11,0	19,0	117,000
320	320	300	11,5	20,5	127,000
340	340	300	12,0	21,5	134,000
360	360	300	12,5	22,5	142,000
400	400	300	13,5	24,0	155,000
450	450	300	14,0	26,0	171,000
500	500	300	14,5	28,0	187,000
550	550	300	15,0	29,0	199,000
600	600	300	15,5	30,0	212,000
650	650	300	16,0	31,0	225,000
700	700	300	17,0	32,0	241,000
800	800	300	17,5	33,0	262,000
900	900	300	18,5	35,0	291,000
1000	1000	300	19,0	36,0	314,000

Ampia gamma disponibile anche in qualità S355J2