


TRAVI HEM EN 10025 - EN 10034

HEM BEAMS EN 10025 - EN 10034



profilo e dimensioni in mm/ section and dimensions in mm					peso weight Kg / Mt
HE	h	b	a	e	
100	120	106	12,0	20,0	41,800
120	140	126	12,5	21,0	52,100
140	160	146	13,0	22,0	63,200
160	180	166	14,0	23,0	76,200
180	200	186	14,5	24,0	88,900
200	220	206	15,0	25,0	103,000
220	240	226	15,5	26,0	117,000
240	270	248	18,0	32,0	157,000
260	290	268	18,0	32,5	172,000
280	310	288	18,5	33,0	189,000
300	340	310	21,0	39,0	238,000
320	359	309	21,0	40,0	245,000
340	377	309	21,0	40,0	248,000
360	395	308	21,0	40,0	250,000
400	432	307	21,0	40,0	256,000
450	478	307	21,0	40,0	263,000
500	524	306	21,0	40,0	270,000
550	572	306	21,0	40,0	278,000
600	620	305	21,0	40,0	285,000
650	668	305	21,0	40,0	293,000
700	716	304	21,0	40,0	301,000
800	814	303	21,0	40,0	317,000
900	910	302	21,0	40,0	333,000
1000	1008	302	21,0	40,0	349,000