


TUBI SS API 5L GR.X42 - ASTM A106 GR.B ...


SEAMLESS STEEL PIPES API 5L GR.X42 - ASTM A106 GR.B ...



diametro / diameter		spessore (s)		peso	diametro / diameter		spessore (s)		peso
pollici	(D)	thickness	schedula	weight	pollici	(D)	thickness	schedula	weight
NPS	mm	mm	schedule nr	Kg / Mt	NPS	mm	mm	schedule nr	Kg / Mt
1/4 "	13,7 x	2,24	40 (STD)	0,63	3 1/2 "	101,6 x	5,74	40 (STD)	13,57
		3,02	80 (XS)	0,80			8,08	80	18,64
3/8 "	17,1 x	2,31	40 (STD)	0,84	4 "	114,3 x	4,78	30	12,91
		3,20	80 (XS)	1,10			6,02	40 (STD)	16,08
2,77	40 (STD)	1,27	8,56	80 (XS)			22,32		
3,73	80 (XS)	1,62	11,13	120			28,32		
1/2 "	21,3 x	4,78	160	1,95	5 "	141,3 x	13,49	160	33,54
		7,47	XXS	2,55			17,12	XXS	41,03
		2,87	40 (STD)	1,69			6,55	40 (STD)	21,77
		3,91	80 (XS)	2,20			9,53	80 (XS)	30,97
3/4 "	26,7 x	5,56	160	2,90	6 "	168,3 x	12,70	120	40,28
		7,82	XXS	3,64			15,88	160	49,12
		3,38	40 (STD)	2,50			19,05	XXS	57,43
		4,55	80 (XS)	3,24			4,78		19,28
1 "	33,4 x	6,35	160	4,24	8 "	219,1 x	6,35		25,36
		9,09	XXS	5,45			7,11	40 (STD)	28,26
		3,56	40 (STD)	3,39			10,97	80 (XS)	42,56
		4,85	80 (XS)	4,47			14,27	120	54,21
1 1/4 "	42,2 x	6,35	160	5,61	10 "	273,0 x	18,26	160	67,57
		9,70	XXS	7,77			21,95	XXS	79,22
		3,68	40 (STD)	4,05			6,35	20	33,32
		5,08	80 (XS)	5,41			7,04	30	36,82
1 1/2 "	48,3 x	7,14	160	7,25	12 "	323,8 x	8,18	40 (STD)	42,55
		10,15	XXS	9,55			10,31	60	53,09
		3,91	40 (STD)	5,44			12,70	80 (XS)	64,64
		5,54	80 (XS)	7,48			6,35	20	41,76
2 "	60,3 x	8,74	160	11,11	10 "	273,0 x	7,80	30	51,01
		11,07	XXS	13,44			9,27	40 (STD)	60,29
		5,16	40 (STD)	8,63			12,70	60 (XS)	81,53
		7,01	80 (XS)	11,41			15,09	80	95,98
2 1/2 "	73,0 x	9,53	160	14,92	12 "	323,8 x	6,35	20	49,71
		14,02	XXS	20,39			8,38	30	65,19
		3,96		8,30			9,53	STD	73,86
		5,49	40 (STD)	11,29			10,31	40	79,71
3 "	88,9 x	7,62	80 (XS)	15,27	12 "	323,8 x	12,70	XS	97,44
		11,13	160	21,35			14,27	60	108,9
		15,24	XXS	27,68			17,48	80	132,1

TUBI SS API 5L GR.X42 - ASTM A106 GR.B ...

SEAMLESS STEEL PIPES API 5L GR.X42 - ASTM A106 GR.B ...



diametro / diameter		spessore (s)		peso	diametro / diameter		spessore (s)		peso
pollici	(D)	thickness	schedula	weight	pollici	(D)	thickness	schedula	weight
NPS	mm	mm	schedule nr	Kg / Mt	NPS	mm	mm	schedule nr	Kg / Mt
14 "	355,6 x	7,92	20	67,91	18 "	457 x	7,92	20	87,71
		9,53	30 (STD)	81,33			9,53	STD	105,2
		11,13	40	94,55			11,13	30	122,4
		12,70	XS	107,4			12,70	XS	139,2
		15,09	60	126,7			19,05	60	205,8
		19,05	80	158,1			23,83	80	254,6
16 "	406,4 x	7,92	20	77,83	20 "	508 x	9,53	20 (STD)	117,2
		9,53	30 (STD)	93,27			12,70	30 (XS)	155,1
		12,70	40 (XS)	123,3			15,09	40	183,4
		16,66	60	160,1			20,62	60	247,8
		21,44	80	203,5			26,19	80	311,2

Disponibili anche in conformità alla EN 10216 P235/P265GH ...

TUBI SS API 5L GR.X42 - ASTM A106 GR.B ... **ZINCATI A CALDO**

UNI EN ISO 1461

GALVANIZED SEAMLESS STEEL PIPES API 5L GR.X42 - ASTM A106 GR.B ...


UNI EN ISO 1461



diametro / diameter		spessore (s)		peso	diametro / diameter		spessore (s)		peso
pollici	(D)	thickness	schedula	weight	pollici	(D)	thickness	schedula	weight
NPS	mm	mm	schedule nr	Kg / Mt	NPS	mm	mm	schedule nr	Kg / Mt
1/2 "	21,3 x	2,77	40 (STD)	1,31	1 1/2 "	48,3 x	3,68	40 (STD)	4,17
		3,73	80 (XS)	1,67			5,08	80 (XS)	5,57
3/4 "	26,7 x	2,87	40 (STD)	1,74	2 "	60,3 x	3,91	40 (STD)	5,60
		3,91	80 (XS)	2,27			5,54	80 (XS)	7,70
1 "	33,4 x	3,38	40 (STD)	2,58	2 1/2 "	73,0 x	5,16	40 (STD)	8,89
		4,55	80 (XS)	3,34	3 "	88,9 x	5,49	40 (STD)	11,63
1 1/4 "	42,2 x	3,56	40 (STD)	3,49	4 "	114,3 x	6,02	40 (STD)	16,56
		4,85	80 (XS)	4,60					

TUBI SS API 5L GR.X52 - ASTM A333 GR. 6° ...

SEAMLESS STEEL PIPES API 5L GR.X52 - ASTM A333 GR. 6°



diametro / diameter (D)		spessore (s)		peso	diametro / diameter (D)		spessore (s)		peso
pollici		thickness	schedula	weight	pollici		thickness	schedula	weight
NPS	mm	mm	schedule nr	Kg / Mt	NPS	mm	mm	schedule nr	Kg / Mt
1/2 "	21,3 x	2,77	40 (STD)	1,27	1 1/2"	48,3 x	5,08	80 (XS)	5,41
		3,73	80 (XS)	1,62			3,91	40 (STD)	5,44
3/4 "	26,7 x	2,87	40 (STD)	1,69	2 "	60,3 x	5,54	80 (XS)	7,48
		3,91	80 (XS)	2,20			5,16	40 (STD)	8,63
1 "	33,4 x	3,38	40 (STD)	2,50	2 1/2 "	73,0 x	7,01	80 (XS)	11,41
		4,55	80 (XS)	3,24			5,49	40 (STD)	11,29
1 1/4 "	42,2 x	3,56	40 (STD)	3,39	3 "	88,9 x	7,62	80 (XS)	15,27
		4,85	80 (XS)	4,47			6,02	40 (STD)	16,08
1 1/2 "	48,3 x	3,68	40 (STD)	4,05	4 "	114,3 x	8,56	80 (XS)	22,32