

PROFILI TONDI EN 10025 - EN 10060 ROUND BARS EN 10025 - EN 10060



diametro diameter (d) mm	peso weight Kg / Mt	diametro diameter (d) mm	peso weight Kg / Mt	diametro diameter (d) mm	peso weight Kg / Mt
6	0,220	40	9,860	125	96,300
8	0,400	42	10,880	130	104,000
10	0,620	45	12,500	140	121,000
12	0,890	50	15,400	150	139,000
14	1,210	55	18,700	160	158,000
15	1,390	60	22,200	170	178,000
16	1,580	65	26,000	180	200,000
18	2,000	70	30,200	190	222,850
20	2,470	75	34,700	200	246,640
22	2,980	80	39,500	210	271,920
24	3,550	85	44,500	220	298,440
25	3,850	90	49,900	230	326,190
26	4,170	95	55,600	240	355,160
28	4,830	100	61,700	250	385,380
30	5,550	105	68,000	260	416,780
32	6,310	110	74,600	270	449,460
35	7,550	115	81,500	280	483,370
38	8,900	120	88,800	300	554,880

PROFILI QUADRI EN 10025 - EN 10059 SQUARE BARS EN 10025 - EN 10059



profilo section (s) mm	peso weight Kg / Mt	profilo section (s) mm	peso weight Kg / Mt	profilo section (s) mm	peso weight Kg / Mt
6	0,280	30	7,070	80	50,200
8	0,498	32	8,040	85	56,700
10	0,785	35	9,620	90	63,600
12	1,130	40	12,600	100	78,500
14	1,540	45	15,900	110	94,990
15	1,770	50	19,600	120	113,040
16	2,010	55	23,700	130	133,000
18	2,540	60	28,300	140	154,000
20	3,140	65	33,200	150	177,000
22	3,800	70	38,500		
25	4,910	75	44,200		

Ampia gamma disponibile anche in qualità S355J2